EISENMANN



DIP PAINTING

COMPETENCE AND KNOW-HOW: DIP PAINTING SYSTEMS BY EISENMANN

THE BENEFITS OF TAILOR-MADE CONCEPTS: WATERBORNE, CONVENTIONAL OR E-COAT



Programmable hoist dip lines allow individual processes for small batches and large workpieces.

Eisenmann is one of the leading suppliers in the world for turnkey paint shops. We employ the newest technologies and expertise gained from years of experience having built several hundred systems.

For all areas of industrial painting, from the contract coater to the automobile industry, Eisenmann is your partner for advanced surface finishing technologies.

Small teams of engineers, working with specialists in environmental, material handling and control technologies, develop individual system concepts.

Eisenmann's ability does not stop with the manufacture of paint lines. As operators of complete automotive painting facilities, our personnel is responsible for running a system economically and achieving the highest surface quality.

Know-how from a single source

Eisenmann offers a complete line of dip painting concepts A turnkey facility. Your new Eisenmann dip-coating line has all including indexing systems for conventional or waterborne paint components in the plant perfectly coordinated with one another: and continuous flow electrophoretic systems (anodic/cathodic watersaving pretreatment, indexing and continuous dip-coating E-coat). This is why Eisenmann is considered one of the leading systems, energy-conserving ovens, rational material flow systems, international manufacturers in this area. and comprehensive PC controls as well as all-inclusive service or operation of the entire system by Eisenmann personnel.

Dip coating is an economical and environmentally-friendly painting process. The key areas of application are automotive To help protect the environment, exhaust air and waste-water components, agricultural machinery, household appliances, purification programs are economically integrated into the metal furniture, construction equipment, electrical devices, design. automobiles and many others.

Heating elements and radiators nowadays are primed by E-coat and then powder-coated.

Perfect coordination

Eisenmann has specialists for all of these disciplines under one roof. You need only one partner to answer all of your questions regarding the implementation of your new coating facility.

FOR THE BEST IN CORROSION PROTECTION: E-COAT

ULTRAFILTRATION: BATH MAINTENANCE AND PAINT RECYCLING



Cathodic E-coat system for automotive parts using a 10-stage pretreatment.

Workpieces to be coated are dipped into a watersoluble paint **The benefits of E-coat:** using a low concentration of paint solids.

By applying a DC power field between the workpiece and the counter electrode, the solid particles in the paint deposit on the workpiece. In the process, an extraordinarily uniform film of paint with outstanding adhesion forms in corners, on edges, and in hard to get to areas.

- Highest quality with best corrosion protection
- Uniform, controllable coating thicknesses
- Excellent coverage in corners and on edges or in difficult to reach areas due to good throw power
- No runs or drips; rework not required
- Highly cost effective through practically loss-free coating in a closed loop system using ultrafiltration
- Can be fully automated for medium or large production runs
- Environmentally friendly because paint is practically solvent-free and no paint sludge forms

Anodic or cathodic E-coat: For every application, the appropriate process.

Depending on your requirements, Eisenmann recommends either a continuous flow or indexing systems for anodic or cathodic dip-coating.

Cathodic E-coat is outstanding for providing excellent coverage in cavities as well as for wrap-around edges. Today it is considered the standard for high quality products, other than within the automotive industry.

A partial stream of the paint is continuously removed from the E-coat tank and fed through the ultrafiltration system. There the solids are retained and returned to be mixed into the bath again. The pigment-free ultrafiltrate is used for rinsing loose paint material, still present after coating, from the workpiece. UF rinsing typically is a multi-stage counterflow process.



Multi-stage rinse with final DI-rinse.



ECONOMICAL AND FLEXIBLE, ALSO FOR SMALL PRODUCTION RUNS: **INDEXING SYSTEMS WITH POWER & FREE CONVEYOR**

When selecting a dip coating process for specific applications, a series of important parameters have to be considered, all of which are important in terms of economy and surface quality.

Eisenmann builds all types of paint dip systems, and based on our experience can always recommend the most applicable one.

Indexing systems are used for relatively low overall throughput as well as for larger workpieces of the same type. They are characterized by a compact design with small dip tank volumes.

This type of system is particularly economical because the lift and lowering stations can be integrated into the otherwise continuous material flow system (overhead power & free or chain conveyor) and transfer to other conveyors is not required.



Diagram of an indexing system with power & free conveyor.



Cathodic E-coat with programmable hoist for automotive parts.



VARIABLE AND VERSATILE FOR ALL SHAPES AND SIZES: PROGRAMMABLE HOIST SYSTEMS

Programmable hoist systems are used whenever workpieces of varying materials, shapes and sizes are to be painted. These systems are valued for their high flexibility and multitask programming possibilities.

The cleaning, pretreatment and E-coat stages are serviced by one or more programmable hoists. Computer controls allow flexible sequences and treatment times in the tanks depending on workpiece and material.



Diagram of a programmable hoist system.



Hoist dip E-coat system for bus cabins.

HIGH VOLUME PRODUCTION WITH UNIFORM WORKPIECES: CONTINUOUS DIP COATING SYSTEMS



Even very large or heavy workpieces, such as this machine assembly, are no problem for a continuous dip painting system.

Continuous systems are well suited for high rates of production and uniform loads; but not for oversized workpiece dimensions.

Required dwell times in pretreatment, dip tanks and curing ovens result at times in a larger system layout than is common with indexing systems with hoist technology. However, they have the relative advantage that workpieces flow directly through the system on overhead or power & free conveyors without having to be transferred to lifting and lowering stations.

This saves on transfer equipment and related control costs.

Continuous dip painting is the most frequently used painting process for radiators.



Diagram of a continuous dip-coating system.

CLEANER PROCESSING TECHNOLOGY: CLEANING AND PRETREATMENT

ENERGY-EFFICIENT AND CLEAN: PAINT CURING OVENS AND EXHAUST AIR PURIFICATION



Pretreatment systems operate solvent-free with wet chemicals and integrate advanced environmental technology.

Bath maintenance and increased bath life for rinse and process baths are not only economical, but are also required by current government regulations. Rinse water is cascaded repeatedly or recirculated through a filtration system.

The life of cleaner baths can be increased relatively easily by a multi-stage approach or through the use of continuous separation of oil and sludge. Still more effective for high concentration is the use of "Carbosep Ultrafiltration" in the cleaner bath recirculation.





Eisenmann builds custom paint curing ovens adapted to technical specifications and economical feasibility with direct and indirect heating using oil, gas, electric or recovered energy in the form of thermal oil, hot water or steam.

Designs range from simple straight-through ovens to elevated multiple pass ovens with energy saving bottom entry and exit and optimized heat energy concept. Indexing systems with programmable hoist utilize a top-loading or continuous oven.

Cathodic top coat curing oven with bottom entry/exit for heat loss prevention.



Thermal oxidizer with heat recovery for purifying exhaust air from the *E*-coat curing oven.

INTELLIGENT CONTROLS: HANDLING AND CONTROLS

SERVICE AND MAINTENANCE





Indexing system with programmable hoist and roller conveyors connecting load and unload stations.

Eisenmann designs and builds customer-specific materialflow systems such as chain conveyors, power & free, skid conveyors, hoist systems, lifting and lowering stations as well as tailormade special conveyors. Combined with intelligent computer systems and software developed solely for this purpose, they form the basis for fully automated production in your company.

Microprocessorbased controls are also being used more frequently for smaller systems. They profit from powerful, yet economic hardware and our software experience gained with large and complex paint lines. We have been able to achieve a technological edge through constant updating of the synergy potential of our conveyor and handling technologies. Preventive maintenance and continuous system improvements are the basis for lasting operational readiness and troublefree operation of your facility.

Eisenmann offers an extensive package of service programs:

- Periodic service
- Full-time service
- Complete service

Facility telemaintenance per PC and internet is the latest trend. Our service technicians remotely monitor your facility per PC from their workstation and, in many cases, reestablish system operations after a malfunction without making an on-site service call.



EISENMANN

Eisenmann Anlagenbau GmbH & Co. KG Tübinger Str. 81, 71032 Böblingen, Germany Phone +49 7031 78-0, Fax +49 7031 78-1000

www.eisenmann.com

2013 © Eisenmann Anlagenbau GmbH & Co. KG I 08-2013

All rights reserved. All text, images, photos and graphics are subject to copyright and other intellectual property laws. Content may only be used with the express permission of Eisenmann Anlagenbau GmbH & Co. KG. All content, including, without limitation, specifications, descriptions and illustrations, are subject to error and change, in particular with regard to ongoing development of our products in line with technological progress. Changes to content will not be proactively communicated. Technical specifications may vary from country to country.